

THE BEST & LAST ROOF COATING YOU'LL EVER USE!



GACOROOF IS IDEAL FOR:

- | | |
|------------------|-----------------------------|
| Metal | Sprayed Polyurethane Foam |
| Tar & Gravel | Low-Pitched Roofs |
| Cap Sheet | Flat Roofs |
| Torchdown | Mobile Homes |
| Composite | RVs & Campers |
| Aged Asphalt | Built-Up Roofs |
| Modified Bitumen | EPDM & Aged TPO* |
| Barrel Tile | *Surface may require primer |

STANDARD COLORS



(FLIP OVER) TO COMPARE
FOR YOURSELF...

WWW.GACORETAIL.COM (866) 422-6489



COMPARE FOR YOURSELF:



Warranty

Can be applied between 32° - 120°

Withstands Permanent Ponding Water

Primer/ Basecoat Required?

Recoating Required?

GACOROOF

**LIMITED
50-YEAR**

YES

YES

NO*

NO

Brand X

5-10 Years

NO

NO

YES

YES

- **2 coat application of same product**
Brand X requires multiple products
- **Withstands permanent ponding water**
Brand X is 48 hours only
- **Temperature application range 32°-120° F**
Brand X is 50°-90° F
- **1-12 hour cure time, dry to the touch**
Brand X is 24-48 hours
- **1 gallon = 100 sq. ft. per coat**
Brand X is 1.5 gallons
- **Can be used on "Flat Roofs"**
Brand X requires 1/4" slope
- **Can be rained on after 2 hours**
Brand X requires no "rain, dew or fog within 24-48 hours"
- **Permanently flexible**
Brand X becomes brittle and begins to degrade over time

- **Recoat can be done after cure time**
Brand X may require 24 hours before recoat
- **Silicone Roof Coating**
Brand X all sell acrylic roof coatings
- **Ponding WaterProof**
Brand X is ponding water Resistant
- **50 year warranty**
Brand X 5-10 years
- **No polyester mat between coats**
Brand X requires
- **UV resistant**
Brand X loses mil thickness due to UV exposure
- **22 mil system**
Brand X is 48-60 mil

*EPDM & Aged TPO may require primer.
Use a GacoRoof Adhesion Test Kit to test for proper adhesion.

